

1		2		3		4		5		6		7		8	
REV.	DESCRIPTION	DRW.	CHK.	APP.	DATE	Ordering information: 21X22564-XXS10X-XXX-A/B						Cir-cuits		Dimension mm	
A	RELEASE					B PBT N Nylon-6T L LCP						L1		L2	
B	增修尺寸檢驗重點及圖面	KEN	王盛富	郭豐榮	97.11.24	Number of Contact 04~80						2X2		2X3	
SPECIFICATIONS Current Rating: 3 Amp Voltage Rating: 230V Insulator resistance: 5000 Megohms Min. Contact Resistance: 20 m ohms Max. Dielectric withstanding: AC 1000V/minute Operating Temperature: -40 ~ +105 C Contact Material: Brass Insulator Material: Polyester UL94V-0 Standard Color: Black Finish: Gold, Tin or Duplex plated Duplex plated: Gold plated on contact area Tin on solder area												2X4		2X5	
												2X6		2X7	
<div style="border: 1px solid black; padding: 2px; display: inline-block;">RoHS Compliant</div>												2X12		2X13	
												2X14		2X15	
												2X20		2X21	
												2X22		2X23	
RECOMMENDED P. C. B. LAYOUT												2X28		2X29	
												2X30		2X31	
<div style="border: 1px solid black; padding: 2px; display: inline-block;">RoHS Compliant</div>												2X36		2X37	
												2X38		2X39	
RECOMMENDED P. C. B. LAYOUT												2X40		2X40	
												2X40		2X40	
RECOMMENDED P. C. B. LAYOUT												2X40		2X40	
												2X40		2X40	
RECOMMENDED P. C. B. LAYOUT												2X40		2X40	
												2X40		2X40	
RECOMMENDED P. C. B. LAYOUT												2X40		2X40	
												2X40		2X40	
RECOMMENDED P. C. B. LAYOUT												2X40		2X40	
												2X40		2X40	
RECOMMENDED P. C. B. LAYOUT												2X40		2X40	
												2X40		2X40	
RECOMMENDED P. C. B. LAYOUT												2X40		2X40	
												2X40		2X40	
RECOMMENDED P. C. B. LAYOUT												2X40		2X40	
												2X40		2X40	
RECOMMENDED P. C. B. LAYOUT												2X40		2X40	
												2X40		2X40	
RECOMMENDED P. C. B. LAYOUT												2X40		2X40	
												2X40		2X40	
RECOMMENDED P. C. B. LAYOUT												2X40		2X40	
												2X40		2X40	
RECOMMENDED P. C. B. LAYOUT												2X40		2X40	
												2X40		2X40	
RECOMMENDED P. C. B. LAYOUT												2X40		2X40	
												2X40		2X40	
RECOMMENDED P. C. B. LAYOUT												2X40		2X40	
												2X40		2X40	
RECOMMENDED P. C. B. LAYOUT												2X40		2X40	
												2X40		2X40	
RECOMMENDED P. C. B. LAYOUT												2X40		2X40	
												2X40		2X40	
RECOMMENDED P. C. B. LAYOUT												2X40		2X40	
												2X40		2X40	
RECOMMENDED P. C. B. LAYOUT												2X40		2X40	
												2X40		2X40	
RECOMMENDED P. C. B. LAYOUT												2X40		2X40	
												2X40		2X40	
RECOMMENDED P. C. B. LAYOUT												2X40		2X40	
												2X40		2X40	
RECOMMENDED P. C. B. LAYOUT												2X40		2X40	
												2X40		2X40	
RECOMMENDED P. C. B. LAYOUT												2X40		2X40	
												2X40		2X40	
RECOMMENDED P. C. B. LAYOUT												2X40		2X40	
												2X40		2X40	
RECOMMENDED P. C. B. LAYOUT												2X40		2X40	
												2X40		2X40	
RECOMMENDED P. C. B. LAYOUT												2X40		2X40	
												2X40		2X40	
RECOMMENDED P. C. B. LAYOUT												2X40		2X40	
												2X40		2X40	
RECOMMENDED P. C. B. LAYOUT												2X40		2X40	
												2X40		2X40	
RECOMMENDED P. C. B. LAYOUT												2X40		2X40	
												2X40		2X40	
RECOMMENDED P. C. B. LAYOUT												2X40		2X40	
												2X40		2X40	
RECOMMENDED P. C. B. LAYOUT												2X40		2X40	
												2X40		2X40	
RECOMMENDED P. C. B. LAYOUT												2X40		2X40	
												2X40		2X40	
RECOMMENDED P. C. B. LAYOUT												2X40		2X40	
												2X40		2X40	
RECOMMENDED P. C. B. LAYOUT												2X40		2X40	
												2X40		2X40	
RECOMMENDED P. C. B. LAYOUT												2X40		2X40	
												2X40		2X40	
RECOMMENDED P. C. B. LAYOUT												2X40		2X40	
												2X40		2X40	
RECOMMENDED P. C. B. LAYOUT												2X40		2X40	
												2X40		2X40	
RECOMMENDED P. C. B. LAYOUT												2X40		2X40	
												2X40		2X40	
RECOMMENDED P. C. B. LAYOUT												2X40		2X40	
												2X40		2X40	
RECOMMENDED P. C. B. LAYOUT												2X40		2X40	
												2X40		2X40	
RECOMMENDED P. C. B. LAYOUT												2X40		2X40	
												2X40		2X40	
RECOMMENDED P. C. B. LAYOUT												2X40		2X40	
												2X40		2X40	
RECOMMENDED P. C. B. LAYOUT												2X40		2X40	
												2X40		2X40	
RECOMMENDED P. C. B. LAYOUT												2X40		2X40	
												2X40		2X40	
RECOMMENDED P. C. B. LAYOUT												2X40		2X40	
												2X40		2X40	
RECOMMENDED P. C. B. LAYOUT												2X40		2X40	
												2X40		2X40	
RECOMMENDED P. C. B. LAYOUT												2X40		2X40	
												2X40		2X40	
RECOMMENDED P. C. B. LAYOUT												2X40		2X40	
												2X40		2X40	
RECOMMENDED P. C. B. LAYOUT												2X40		2X40	
												2X40		2X	